

## GS-1 - Artillian Horse Blinders ™

Installation Instructions

These instructions assume a factory installation of your John Deere Auxiliary Work Lights with John Deere Brush Guards mounted in the factory positions on the ROPS.

- 1. From behind the tractor, tilt one of the light housings ① forward.
- 2. Disconnect the electrical connector 2. Tuck the wire out of the way.
- 3. Unscrew the nut 4 from the mounting screw 3 (13mm tools).
- 4. Remove the nut and the light from the tractor, keeping both items within reach. The screw should remain in place.
- 5. Note that there is a LEFT and RIGHT shroud (see image). Grasp the appropriate shroud at the ends holding it in the same orientation as shown in the image.
- 6. Wrap the ends down and under to make a tubular shape so that the two slotted holes become mated at the bottom.
- 7. Set the overlapped slots in the shroud over the mounting screw. The shroud should be sitting with the bulge pointing toward the front of the tractor and toward the inside of the tractor.
- 8. Holding the shroud in place with one hand or a helper, replace the light housing back onto the mounting screw, nested inside of the shroud. Then, while holding the shroud and light housing with one hand, screw the nut on the mounting screw until finger tight with your other hand. It is now ok to let go of everything.
- 9. Tighten the nut with your tools until tension is *barely noticeable*. You should be able to nudge the shroud and light housing around but remain in place when you let go of them.
- 10. Adjust the light housing and shroud to the positions desired. You may temporarily reconnect the power wire and try it from the seat. Be sure to align the shroud to be in line with the light housing. The slots in the shroud allow for a small amount of adjustment.
- 11. Once satisfied, tighten the *screw* while keeping the *nut* still. This way, the light housing and shroud will not move as you cinch the fastener.
- 12. Reattach the electrical connector and tilt the work light housing back to the normal position.
- 13. Repeat on other side of tractor and enjoy!





