



60" | 72" HYDRAULIC ANGLING PLOW



*Artillian 72" Plow (PN: SPA-72HYD)
on Kubota Skid Steer Attachments
Shown with Optional - Blade Markers*

Fits (2015+) Artillian Pallet Fork Frame

ARTILLIAN PLOW INCLUDES

Steel Moldboard Assembly	Plow Trip Frame
A-Frame Assembly	2 Hydraulic Cylinders
Mounting Frame	Hydraulic Hose Assembly
Cross-Over Relief Valve Block	A-Frame Pinch Guard

ARTILLIAN PLOW REQUIRES



John Deere QA Pallet Fork Frame



Skid Steer QA Pallet Fork Frame

ARTILLIAN QUALITY ACCESSORIES

DIVERTER KITS

Add a third hydraulic circuit to your loader for operating our Grapple, Plow Adapters or other hydraulic loader attachments of your choosing.



SQUARE/RECTANGULAR OR ROUND ROPS-MOUNT DIRECTIONAL WORK LIGHTS

Internal compression spring lets you disengage the light by pulling out on the built-in grab handle, rotating the light up to 360 degrees, then re-engaged to the desired position. All without tools!



HYDRAULIC SPLITTER MANIFOLDS

Double or Triple configurations of our Grapple require one of these manifolds to split the hydraulic fluid to each cylinder.





60" | 72" HYDRAULIC ANGLING PLOW

Quickly Switch Between Plow and Bucket for Stacking Snow

Leave Loader On

Hydraulic Angling

Requires Pallet Fork Frame & Diverter Kit or Extension Hose Kit

1/2 Inch Diameter Skid Shoes

Optional: Blade Markers



Optional: Rubber Extension Wings

Optional: Rubber Snow Deflector

Installed Weight is Approximately 200 lbs. plus 85 lbs. for Pallet Fork Frame

Plow Mounting Frame Included



ATTACHES DIRECTLY TO THE ARTILLIAN PALLET FORK FRAME

ARTILLIAN PLOW WHEEL TRACK ILLUSTRATION

Rear Wheel Track Width	Moldboard Width	Artillian Plow P/N
≤ 52"	60"	SPA-60HYD
≤ 62"	72"	SPA-72HYD
> 62"	> 72"	N/A

The Artillian Hydraulic Plow can angle up to 30° in either direction. In order to ensure that the plow moldboard is always wider than the tractor tires, measure your tractor's rear wheel track width, as shown in the illustration below. Based on this dimension, choose the appropriate plow part number from the table to the right.

